



ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-3 = $136\Omega \pm 12\%$.
PIN 4-6 = $136\Omega \pm 12\%$.
2. INDUCTANCE PARALLEL (@200Hz, 0.78Vrms) :
PIN 1-3 = 3.8H MIN.
RESISANCE PARALLEL 7500Ω MIN.
3. LEAKAGE INDUCTANCE (@1KHz, 0.1Vrms) :
PIN 1-3 (4-6 SHORT) = 6mH TYP.
4. INSERTION LOSS (@2KHz, 0dBm) :
PIN 1-3 (4-6 W/H 600Ω) = 2dB MAX.
5. FREQ RESP (@REF 2KHz) :
FROM 200Hz~4KHz = ± 0.25 dB.
6. RETURN LOSS (4-6 W/H 360Ω/56nF) :
FROM 200Hz~4KHz = 24dB MIN.
7. TURN RATIO (@12KHz, 1Vrms) :
PIN 1-3 : 4-6 = 1 $\pm 1\%$.
8. HI-POT (@4.6KVAC, 1mA, 1MIN) : P-S
9. REEL PACKING.
10. RoHS COMPLIANTE

TOLERANCE : ± 0.25